

(+48) 32 453 91 70 🖂 info@pol-eko.com.pl www.pol-eko.com.pl **POL-EKO A.Polok-Kowalska sp.k.** 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

# Data sheet

# Laboratory Incubator CLN 115 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

### Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen

- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarmAdmin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download



Smart PRO - preview screen






### **TECHNICAL DATA**

air convection	natural
chamber capacity [I]	112
working capacity [I]	112
controller	microprocessor PID
display	7" full colour touch screen
TEMPERATURE	
temperature range [°C]	5°C above ambient temperature +100°C
temperature resolution every [°C]	0,1
temperature fluctuation at 37°C [+/-°C]*	0,2
temperature variation at 37°C [+/-°C]*	0,8
temperature protection	class 3.1 to DIN 12880
CHAMBER	
door type	double(5) / door with viewing window (option)
interior	
Smart PRO	acid-proof stainless steel to DIN 1.4301
IG Smart PRO	acid-proof stainless steel to DIN 1.4301
housing	
Smart PRO	powder coated sheet
IG Smart PRO	stainless steel linen finish

#### overall dims [mm] /1/

width A	660
height B	850
depth C	710
internal dims [mm]	
width D	460
height E	540
depth F	450



shelves (standard   max)	2   7
max shelf workload [kg] /2/	25
- reinforced shelf version (PW) [kg] /3/	50
max unit workload [kg]	60
- reinforced unit version (W) [kg] /4/	120
weight [kg]	65





#### **ELECTRICAL PARAMETERS**

voltage**	230V 50-60Hz
nominal power [W]	450
warranty	24 months
manufacturer	POL-EKO

all the above technical data refer to standard units (without optional accessories)

\* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K= +/- (T average max. - T average min. ) / 2

 $\ast\ast$  - other power supplies on request

1 - depth doesn't include 50 mm of power cable, the width does not include the 20 mm of rubber plug

- 2 on uniformly loaded surface
- 3 reinforced shelf

4 - additional internal glass door

# **OPTIONS AND ACCESSORIES**

INOX

Order number: \*/PP

Order number: \*/A

Order number: \*/PW





KG



Order number: \*/P INOX Order number: KUW GN\*/\* Order number: QLK\* Order number: \*/S or \*/S INOX Order number: \*/ST or \*/S INOX Order number: \*/W Order number: OWW/OWW LED

door with viewing window

Stainless steel wire shelf INOX

Perforated shelf

Reinforced shelf

Stainless steel cuvettes

Castors

Table with castors

Base on castors

Reinforced version

Interior lighting

Order number: PT 100

Additional temperature sensor

Bank: ING BŚ o/Wodzisław Śląski | Nr rachunku: 90 1050 1403 1000 0022 0879 5498 | Nr rej. w BDO 000005609 NIP: 647-216-26-87 | REGON: 276111984 | Sąd Rejonowy w Gliwicach, X Wydział Gospodarczy | KRS 0001009595



HEPA 

Order number: HEPA >0<

Order number: BRT/\*/L or IQ/OQ/PQ

Order number: BPP 12

ALARM 

4

LAN

20mm

30mm

60mm

100mm

(((●)))

Order number: LANK

Order number: PORT ALARM

Order number: OCZ/20

Order number: OCZ/30

Order number: OCZ/60

Order number: OCZ/100

Order number: KD

**HEPA Clean Air Filter** 

Calibration and IQ, OQ, PQ qualification

Battery backup for display

Dry alarm contact

LAN cable

Non-standard access port 20 mm

Additional access port 30 mm

Non-standard access port 60 mm

Non-standard access port 100 mm

Access control

