

(+48) 32 453 91 70

info@pol-eko.com.pl

www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k.
 44-300 Wodzisław Śląski
 ul. Kokoszycka 172 C

Data logger RT 2014 2T

Data sheet



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Standard equipment

- GSM antenna
- micro SD card with SD adapter
- USB power cable with adapter
- Avia software to be downloaded from www
- selected temperature/humidity sensor








0	POL-EKO A.Polok-Kowalska sp.k.		
	44-300 Wodzisław Śląski		
	ul. Kokoszycka 172 C		

TECHNICAL DATA		
controller	microprocessor	
display	OLED 128x64 px	
housing	aluminium	

overall dims [mm]		
width A	72	
height B	85	
depth C	20	
weight [kg]	0,165	
weight [kg]	0,165	



BASIC PARAMETERS	
run time (battery)	40 h
GSM frequency band [MHz]	2G 850/900/1800/1900
number of telephone numbers for sending SMS notifications	5
temperature measurement	external Pt 100
temperature measurement range (according to sensor) [°C]	-110 +400 (depending on sensor type)
temperature measurement resolution (-40+200°C) [°C]	0,1
temperature measurement accuracy (-40+200°C) [°C]	+/- 0,5
humidity measurement	external RH_STD / RH_PREM
humidity measurement range [%]	RH_STD: 080 RH_PREM: 0100
humidity measurement resolution [%]	1
humidity measurement accuracy [%]	RH_STD: 1,8 RH_PREM: 0,8
sensor cable length [m]	2,5
data recording interval [min]	1/5/15/30/60
internal memory	1 mln
additional (external) memory	microSD 4 GB card
port	micro USB
ELECTRICAL PARAMETERS	
voltage**	5 VDC
warranty	24 months
manufacturer	POL-EKO

OPTIONS AND ACCESSORIES





(+48) 32 453 91 70info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

0

Order number: PT 100 L

Order number: PT 100 S

Order number: PT 100 H

Order number: RT 2014 RH_STD

Order number: RT 2014 RH_PREM

Order number: RT 2014_FIT

Order number: RT 2014_IN

Order number: RT 2014_OUT

Standard temperature sensor

Temperature sensor for low temperatures

Temperature sensor for high temperatures

Standard humidity and temperature sensor

Premium humidity and temperature sensor

Holder

Binary input

Binary output

