

(+48) 32 453 91 70

info@pol-eko.com.pl

www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski

ul. Kokoszycka 172 C

Laboratory Refrigerator CHL 2/2 Smart

Data sheet



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART controller:

- 4,3", clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage
- event registry
- user manual for direct download
- Quick change of program parameters
- Alarm Bar
- operating with gloves on



Smart - preview screen






POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

1 110 CHL 2/2 Smart type **TECHNICAL DATA** air convection forced 150 / 150 chamber capacity [I] 122 / 122 working capacity [I] controller microprocessor PID display 4,3" full colour touch screen **TEMPERATURE** temperature range [°C] 0...+15 temperature resolution every ... [°C]0,1 temperature fluctuation at 4°C [+/-°C]* 0,4 temperature variation at 4°C [+/-°C]* 0,7 temperature protection class 1.0 to DIN 12880 / class 3.2 (option) **CHAMBER** door type solid / glass or double (option) /4/ interior C Smart stainless steel to DIN 1.4016 CS Smart stainless steel to DIN 1.4016 P Smart acid-proof stainless steel to DIN 1.4301 acid-proof stainless steel to DIN 1.4301 PS Smart housing C Smart powder coated sheet CS Smart stainless steel polished P Smart powder coated sheet PS Smart stainless steel polished

overall (dims	[mm]	/1/
-----------	------	------	-----

width A	600
height B	1720
depth C	650
internal dims [mm]	
width D	480
width D'	520
height E	660
depth F	420
depth F'	480
depth G	320
height H	440



shelves (standard max)	3 4 / 3 4
max shelf workload [kg] /2/	10
max unit workload [kg]	30 / 30
weight [kg]	109





POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

ELECTRICAL PARAMETERS	
voltage**	230V 50-60Hz
nominal power [W]	500
refrigerant	R1234ze / GWP=7
warranty	24 months
manufacturer	POL-EKO
txt_opis_pt	all the above technical data refer to standard units (without optional accessories) * - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as: K= +/- (T average max T average min.) / 2; parameters given for the chamber above the bottom step ** - other power supplies on request 1 - depth doesn't include 50 mm of power cable, the width does not include the 20 mm of rubber plug 2 - on uniformly loaded surface 3 - reinforced shelf 4 - additional internal glass door
PL typ urządzenia	Laboratory Refrigerator
img_photo	CHL-2-2-Smart
The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.	The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.
nazwa www pl	Chłodziarka Laboratoryjna CHL 2/2 Smart
nazwa www EN	Laboratory Refrigerator CHL 2/2 Smart
nazwa www ES	Refrigerador de Laboratorio CHL 2/2 Smart
ekran_grafika	chl_smart
	chłodziarki laboratoryjne
	chłodziarki laboratoryjne dwukomorowe
0	1

all the above technical data refer to standard units (without optional accessories)

- * fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as: K= +/- (T average max. T average min.) / 2; parameters given for the chamber above the bottom step
- ** other power supplies on request
- 1 depth doesn't include 50 mm of power cable, the width does not include the 20 mm of rubber plug
- 2 on uniformly loaded surface
- 3 reinforced shelf
- 4 additional internal glass door

OPTIONS AND ACCESSORIES



Order number: */C Internal glass door



Order number: */A External glass door



Order number: */P INOX Stainless steel wire shelf INOX



Order number: */PP Perforated shelf





POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C



Order number: */PW Reinforced shelf



Order number: KUW GN*/* Stainless steel cuvettes



Order number: ST/CHL/SWP ALU Aluminum drawer with powder coated slides



Order number: ST/CHL/SWP INOX Stainless steel drawer with powder coated slides



Order number: ST/CHL/SWPN INOX Stainless steel drawer with stainless steel slides



Order number: *PLUS Automatic defrosting function



Order number: GNZ Internal socket



Order numberLabDesk LabDesk software



Order number: BRT/*/L or IQ/OQ/PQ Calibration and IQ, OQ, PQ qualification

DIN 3.2

Order number: */3.2 Over temperature protection 3.2 class according to DIN 12880



Order number: BPP 12 Battery backup for display



Order number: PORT ALARM Dry alarm contact



Order number: LANK LAN cable



Order number: OCZ/20 Non-standard access port 20 mm



Order number: OCZ/30 Additional access port 30 mm



Order number: OCZ/60 Non-standard access port 60 mm



Order number: OCZ/100 Non-standard access port 100 mm





POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C



Order number: KD

Access control

