

- (+48) 32 453 91 70
- info@pol-eko.com.pl

 info@pol-eko.com
- www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

Data sheet SLN 53 SIMPLE



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.








(+48) 32 453 91 70info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

TECHNICAL DATA	
air convection	natural
chamber capacity [I]	56
working capacity [I]	56
controller	microprocessor with external display
display	LCD
TEMPERATURE	
temperature range [°C]	5°C above ambient temperature +250°C
temperature resolution every [°C]	0,1
temperature fluctuation at 105°C [+/-°C]*	0,3
temperature variation at 105°C [+/-°C]*	2,5
temperature protection	class 1.0 to DIN 12880
CHAMBER	
door type	solid
interior	stainless steel to DIN 1.4016
housing	powder coated sheet

overall dims [mm] /1/

width A	660
height B	590
depth C	620
internal dims [mm]	
width D	390
height E	390
depth F	350



shelves (standard max)	2 5
max shelf workload [kg] /2/	10
max unit workload [kg]	40
weight [kg]	46



⟨+48⟩ 32 453 91 70⋈ info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

ELECTRICAL PARAMETERS		
voltage**	230V 50-60Hz	
nominal power [W]	1700	
warranty	24 months	
manufacturer	POL-EKO	

all the above technical data refer to standard units (without optional accessories)

st - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K = +/- (T average max. - T average min.) / 2

** - other power supplies on request

1 - depth doesn't include 50 mm of power cable, the width does not include the 20 mm of rubber plug

OPTIONS AND ACCESSORIES



Order number: */P INOX Stainless steel wire shelf INOX



Order number: */PP Perforated shelf



Order number: BRT/*/L or IQ/OQ/PQ Calibration and IQ, OQ, PQ qualification

