

(+48) 32 453 91 70 🖂 info@pol-eko.com.pl www.pol-eko.com.pl **POL-EKO A.Polok-Kowalska sp.k.** 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

Data sheet

Drying Oven SLN 75 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen

- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarmAdmin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download



Smart PRO - preview screen






1	152
type	SLN 75 Smart PRO
TECHNICAL DATA	
air convection	natural
chamber capacity [I]	75
working capacity [I]	75
controller	microprocessor PID
display	7" full colour touch screen
TEMPERATURE	
temperature range [°C]	5°C above ambient temperature +300°C
temperature resolution every [°C]	0,1
temperature protection	class 3.1 to DIN 12880
CHAMBER	
door type	solid / door with viewing window (option)
interior	
Smart PRO	acid-proof stainless steel to DIN 1.4301
IG Smart PRO	acid-proof stainless steel to DIN 1.4301
housing	
Smart PRO	powder coated sheet
IG Smart PRO	stainless steel linen finish

overall dims [mm] /1/

width A	590
height B	850
depth C	620
internal dims [mm]	
width D	400
height E	530
depth F	360



shelves (standard max)	2 5
max shelf workload [kg] /2/	25
- reinforced shelf version (PW) [kg] /3/	50
max unit workload [kg]	40
- reinforced unit version (W) [kg] /4/	80
weight [kg]	60





ELECTRICAL PARAMETERS

voltage**	230V 50-60Hz		
nominal power [W]	1700		
warranty	24 months		
manufacturer	POL-EKO all the above technical data refer to standard units (without optional accessories) * - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as: K= +/- (T average max T average min.) / 2 ** - other power supplies on request 1 - depth doesn't include 50 mm of power cable 2 - on uniformly loaded surface 3 - reinforced shelf 4 - reinforced version		
txt_opis_pt			
PL typ urządzenia	Drying Oven		
img_photo	SLN-75-Smart-PRO		
The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.	The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.		
nazwa www pl	Suszarka Laboratoryjna SLN 75 Smart PRO		
nazwa www EN	Drying Oven SLN 75 Smart PRO		
nazwa www ES	Estufa de Secado SLN 75 Smart PRO		
ekran_grafika	sln_smart_pro		
	Suszarki Laboratoryjne		
0	1		

all the above technical data refer to standard units (without optional accessories)

* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K= +/- (T average max. - T average min.) / 2

** - other power supplies on request

1 - depth doesn't include 50 mm of power cable

2 - on uniformly loaded surface

3 - reinforced shelf

4 - reinforced version

OPTIONS AND ACCESSORIES



INOX

Order number: */A

Order number: */P INOX

Order number: */PP

door with viewing window

Stainless steel wire shelf INOX

Perforated shelf

Order number: */PW

Reinforced shelf



Order number: KUW GN*/*

Stainless steel cuvettes

Bank: ING BŚ o/Wodzisław Śląski | Nr rachunku: 90 1050 1403 1000 0022 0879 5498 | Nr rej. w BDO 000005609 NIP: 647-216-26-87 | REGON: 276111984 | Sąd Rejonowy w Gliwicach, X Wydział Gospodarczy | KRS 0001009595



Order number: QLK*

Order number: */S or */S INOX

Order number: */ST or */S INOX

Order number: OWW/OWW LED











HEPA

>0<

4

Order	number:	PT	100

Order number: */W

Order number: HEPA

Order number: BRT/*/L or IQ/OQ/PQ

Order number: PORT ALARM

Order number: BPP 12

ALARM



 (\mathbf{i})

20mm

30mm

60mm

 (\mathbf{I})

100mm

Order number: LANK

Order number: OCZ/20

Order number: OCZ/30

Order number: OCZ/60

Order number: OCZ/100



Order number: KD

Castors

Table with castors

Base on castors

Reinforced version

Interior lighting

Additional temperature sensor

HEPA Clean Air Filter

Calibration and IQ, OQ, PQ qualification

Battery backup for display

Dry alarm contact

LAN cable

Non-standard access port 20 mm

Additional access port 30 mm

Non-standard access port 60 mm

Non-standard access port 100 mm

Access control

