



## Data sheet

print date: 2026-03-12


## Drying Oven SLW 1000 Smart



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

### Advantages of the SMART controller:

- 4,3", clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage
- event registry
- user manual for direct download
- Quick change of program parameters
- Alarm Bar
- operating with gloves on



Smart - preview screen



**TECHNICAL DATA**

air convection	forced
chamber capacity [l]	1220
working capacity [l]	998
controller	microprocessor PID
display	4,3" full colour touch screen

**TEMPERATURE**

temperature range [°C]	5°C above ambient temperature ... +300°C
temperature resolution every ... [°C]	0,1
temperature fluctuation at 105°C [±/°C]*	0,6
temperature variation at 105°C [±/°C]*	3
temperature protection	class 2.0 to DIN 12880 / class 3.1 (option)

**CHAMBER**

door type	solid / door with viewing window (option)
<b>interior</b>	
Smart	acid-proof stainless steel to DIN 1.4301
IG Smart	acid-proof stainless steel to DIN 1.4301
<b>housing</b>	
Smart	powder coated sheet
IG Smart	stainless steel linen finish

**overall dims [mm] /1/**

width A	1260
height B	2000
depth C	880

**internal dims [mm]**

width D	1040
height E	1610
depth F	600



shelves (standard   max)	6   22
- reinforced shelf version (PW) [kg] /3/	100
max unit workload [kg]	300
- reinforced unit version (W) [kg] /4/	300
weight [kg]	307




**ELECTRICAL PARAMETERS**


voltage	400V 50/60Hz
nominal power [W]	5500
warranty	24 months
manufacturer	POL-EKO®

all the above technical data refer to standard units (without optional accessories)  
 \* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:  
 $K = \pm (T \text{ average max.} - T \text{ average min.}) / 2$   
 \*\* - other power supplies on request  
 1 - depth doesn't include 50 mm of power cable  
 2 - on uniformly loaded surface  
 3 - reinforced shelf  
 4 - reinforced version


**OPTIONS AND ACCESSORIES**




Order number: \*/A door with viewing window



Order number: \*/PP Perforated shelf



Order number: \*/PW Reinforced shelf



Order number: KUW GN\*/\* Stainless steel cuvettes




Order number: OWW/OWW LED Interior lighting



Order number: HEPA HEPA Clean Air Filter



Order number: LabDesk LabDesk software



Order number: BRT\*/L or IQ/OQ/PQ Calibration and IQ, OQ, PQ qualification



Order number: \*/3.1 Over temperature protection 3.1 class according to DIN 12880



Order number: KD Access control



Order number: RFID LOCK (SMART) RFID LOCK (SMART)



Order number: BPP 12

Battery backup for display



Order number: PORT ALARM

Dry alarm contact



Order number: LANK

LAN cable



Order number: OCZ/20

Non-standard access port 20 mm



Order number: OCZ/30

Additional access port 30 mm



Order number: OCZ/60

Non-standard access port 60 mm



Order number: OCZ/100

Non-standard access port 100 mm