

(+48) 32 453 91 70
info@pol-eko.com.pl

www.pol-eko.com.pl

Data sheet

Drying Oven SLW 750 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen

- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download



Smart PRO - preview screen






1	162
type	SLW 750 Smart PRO
TECHNICAL DATA	
air convection	forced
chamber capacity [I]	749
working capacity [I]	749
controller	microprocessor PID
display	7" full colour touch screen
TEMPERATURE	
temperature range [°C]	5°C above ambient temperature +300°C
temperature resolution every [°C]	0,1
temperature fluctuation at 105°C [+/-°C]*	0,6
temperature variation at 105°C [+/-°C]*	2,5
temperature protection	class 3.1 to DIN 12880
CHAMBER	
door type	solid / door with viewing window (option)
interior	
Smart PRO	acid-proof stainless steel to DIN 1.4301
IG Smart PRO	acid-proof stainless steel to DIN 1.4301
housing	
Smart PRO	powder coated sheet
IG Smart PRO	stainless steel linen finish

overall dims [mm] /1/

width A	1260
height B	1600
depth C	880
internal dims [mm]	
width D	1040
height E	1200
depth F	600



shelves (standard max)	5 16
- reinforced shelf version (PW) [kg] /3/	100
max unit workload [kg]	140
- reinforced unit version (W) [kg] /4/	300
weight [kg]	260





ELECTRICAL PARAMETERS

voltage**	400V 50-60Hz
nominal power [W]	5500
warranty	24 months
manufacturer	POL-EKO
txt_opis_pt	all the above technical data refer to standard units (without optional accessories) * - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as: K= +/- (T average max T average min.) / 2 ** - other power supplies on request 1 - depth doesn't include 50 mm of power cable 2 - on uniformly loaded surface 3 - reinforced shelf 4 - reinforced version
PL typ urządzenia	Drying Oven
img_photo	SLW-750-Smart-PRO
The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.	The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.
nazwa www pl	Suszarka Laboratoryjna SLW 750 Smart PRO
nazwa www EN	Drying Oven SLW 750 Smart PRO
nazwa www ES	Estufa de Secado SLW 750 Smart PRO
ekran_grafika	sl_smart_pro
	Suszarki Laboratoryjne
0	1

all the above technical data refer to standard units (without optional accessories)

* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K= +/- (T average max. - T average min.) / 2

** - other power supplies on request

1 - depth doesn't include 50 mm of power cable

2 - on uniformly loaded surface

3 - reinforced shelf

4 - reinforced version

OPTIONS AND ACCESSORIES



INOX

Order number: */A

Order number: */P INOX

Order number: */PP

Order number: */PW

door with viewing window

Stainless steel wire shelf INOX

Perforated shelf

Reinforced shelf



Order number: KUW GN*/*

Stainless steel cuvettes

Bank: ING BŚ o/Wodzisław Śląski | Nr rachunku: 90 1050 1403 1000 0022 0879 5498 | Nr rej. w BDO 000005609 NIP: 647-216-26-87 | REGON: 276111984 | Sąd Rejonowy w Gliwicach, X Wydział Gospodarczy | KRS 0001009595



Order number: */W


Order number: OWW/OWW LED

KG

KG







Order number: PT 100

>0<



LAN

20mm

30mm

60mm

100mm

(((●)))

Order number: BPP 12

Order number: PORT ALARM

Order number: BRT/*/L or IQ/OQ/PQ

Order number: LANK

Order number: OCZ/20

Order number: OCZ/30

Order number: OCZ/60

Order number: OCZ/100

Order number: KD

Reinforced version

Interior lighting

Additional temperature sensor

HEPA Clean Air Filter

Calibration and IQ, OQ, PQ qualification

Battery backup for display

Dry alarm contact

LAN cable

Non-standard access port 20 mm

Additional access port 30 mm

Non-standard access port 60 mm

Non-standard access port 100 mm

Access control

