



POL-EKO
Perfect Environment

(+48) 32 453 91 70
info@pol-eko.com.pl
www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k.
44-300 Wodzisław Śląski
ul. Kokoszycka 172 C

Data sheet





1

type

TECHNICAL DATA

air convection

chamber capacity [l]

working capacity [l]

number of boxes 133x133x50mm (option) [pcs]

controller

display

insulation type

TEMPERATURE

TEMPERATURE AND HUMIDITY

temperature range [°C]

Working temperature range without humidity [°C]

Temperature variation (spatial) at 40°C [±°C]

Temperature fluctuation (time) at 40°C [±°C]

Working temperature range with humidity [°C]

temperature resolution every ... [°C]

Temperature variation (spatial) at 40°C, 75% RH [°C]

Temperature fluctuation (time) at 40°C, 75% RH [°C]

Temperature variation (spatial) at 25°C, 60% RH [°C]

Temperature fluctuation (time) at 25°C, 60% RH [°C]

cooling time from +20°C to -80°C [min]

heating time in case of power failure -80°C to -60°C [min]

Temperature accuracy at 20°C [±°C]*

temperature fluctuation at 37°C [±°C]*

temperature fluctuation at 105°C [±°C]*

temperature fluctuation at 4°C [±°C]*

temperature fluctuation at -20°C [±°C]*

temperature fluctuation at -80°C [±°C]*

temperature variation at 25°C and 60%RH [±°C]*

temperature variation at 37°C [±°C]*

temperature variation at 105°C [±°C]*

temperature variation at 4°C [±°C]*

temperature variation at -20°C [±°C]*

temperature variation at -80°C [±°C]*

temperature fluctuation at 25°C and 60%RH [±°C]*

Temperature recovery time after 30 seconds door opening at 37°C [min]

temperature protection

CO₂

CO₂ range [%]

CO₂ resolution every ... [%]

CO₂ measurement

CO₂ recovery time after 30 seconds door opening at 5 Vol.-% CO₂ [min]

relative humidity range [%]

humidity resolution every ... [%]



humidity variation at 25°C and 60% rH [%rH]

Stabilność wilgotności w 25°C i 60%rH [%rH]

Humidity variation (spatial) at 40°C, 75% RH [+/-%RH]

Humidity fluctuation (time) at 40°C, 75% RH [+/-%RH]

Humidity variation (spatial) at 25°C, 60% RH [+/-%RH]

Humidity fluctuation (time) at 25°C, 60% RH [+/-%RH]

Recovery time to set values after 30 sec door open at 40°C, 75% RH [min]



CHAMBER

door type

interior

B Smart

C Smart

CS Smart

P Smart

PS Smart

Smart

IG Smart

C Smart PRO

CS Smart PRO

P Smart PRO

PS Smart PRO

Smart PRO

IG Smart PRO

housing

B Smart

C Smart

CS Smart

P Smart

PS Smart

Smart

IG Smart

C Smart PRO

CS Smart PRO

P Smart PRO

PS Smart PRO

Smart PRO

IG Smart PRO



POL-EKO
Perfect Environment

(+48) 32 453 91 70
info@pol-eko.com.pl
www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k.
44-300 Wodzisław Śląski
ul. Kokoszycka 172 C

overall dims [mm] /1/

width A

height B

depth C

internal dims [mm]

width D

width D'

height E

depth F

depth F'

depth G

height G

height H

height I



shelves (standard | max)

max shelf workload [kg] /2/

number of internal chambers

number of drawers

max drawer workload [kg]

- reinforced shelf version (PW) [kg] /3/

max unit workload [kg]

- reinforced unit version (W) [kg] /4/

External water tank capacity [l]

weight [kg]

ELECTRICAL PARAMETERS

Energy consumption at 37°C [Wh/h]

voltage**

Energy consumption at 25°C, 60% RH [Wh/h]

Energy consumption at 40°C, 75% RH [Wh/h]

nominal power [W]

refrigerant

Noise level [db(A)]

warranty

manufacturer

txt_opis_pt

PL typ urządzenia

img_photo

The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

nazwa www pl

nazwa www EN

nazwa www ES

ekran_grafika

0



Bank: ING BŚ o/Wodzisław Śląski | **Nr rachunku:** 90 1050 1403 1000 0022 0879 5498 | **Nr rej. w BDO** 000005609
NIP: 647-216-26-87 | **REGON:** 27611984 | Sąd Rejonowy w Gliwicach, X Wydział Gospodarczy | **KRS** 0001009595