

(+48) 32 453 91 70
 □ info@pol-eko.com.pl
 www.pol-eko.com.pl

Data sheet


Laboratory Freezer ZLN-T 200 Smart



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART controller:

- 4,3", clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage
- event registry
- user manual for direct download
- Quick change of program parameters
- Alarm Bar
- operating with gloves on



Smart - preview screen






1	22
type	ZLN-T 200 Smart
TECHNICAL DATA	
air convection	natural
chamber capacity [l]	210
working capacity [I]	180
controller	microprocessor PID
display	4,3" full colour touch screen
insulation type	polyurethane foam
TEMPERATURE	
temperature range [°C]	-400
temperature resolution every [°C]	0,1
temperature fluctuation at -20°C [+/-°C]*	0,5
temperature variation at -20°C [+/-°C]*	2,5
temperature protection	class 3.2 to DIN 12880 (option)
CHAMBER	
door type	solid
interior	
C Smart	stainless steel to DIN 1.4016
CS Smart	stainless steel to DIN 1.4016
P Smart	acid-proof stainless steel to DIN 1.4301
PS Smart	acid-proof stainless steel to DIN 1.4301
housing	
C Smart	powder coated sheet
CS Smart	stainless steel polished
P Smart	powder coated sheet
PS Smart	stainless steel polished

overall dims [mm] /1/

	820
width A	820
height B	1380
depth C	810
internal dims [mm]	
width D	450
width D'	520
height E	770
depth F	520
depth F'	530



shelves (standard max)	2 4
max shelf workload [kg] /2/	10
- reinforced shelf version (PW) [kg] /3/	50
max unit workload [kg]	65



 Bank: ING BŚ o/Wodzisław Śląski
 Nr rachunku:
 90 1050 1403 1000 0022 0879 5498
 Nr rej. w BDO 000005609

 NIP:
 647-216-26-87
 REGON:
 276111984
 Sąd Rejonowy w Gliwicach, X Wydział Gospodarczy
 KRS 0001009595



S	(+48) 32 453 91 70
\bowtie	info@pol-eko.com.pl
\bigoplus	www.pol-eko.com.pl

- reinforced unit version (W) [kg] /4/

weight [kg]

130 120





ELECTRICAL PARAMETERS

voltage**	230V 50-60Hz
nominal power [W]	450
refrigerant	R290 / GWP=3
warranty	24 months
manufacturer	POL-EKO
txt_opis_pt	all the above technical data refer to standard units (without optional accessories) * - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as: K = +/- (T average max T average min.) / 2 ** - other power supplies on request 1 - depth doesn't include 50 mm of power cable 2 - on uniformly loaded surface 3 - reinforced shelf 4 - reinforced version
PL typ urządzenia	Laboratory Freezer
img_photo	ZLN-T-200-Smart
The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.	The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.
nazwa www pl	Zamrażarka Laboratoryjna ZLN-T 200 Smart
nazwa www EN	Laboratory Freezer ZLN-T 200 Smart
nazwa www ES	Congelador de Laboratorio ZLN-T 200 Smart
ekran_grafika	zl_smart
	zamrażarki laboratoryjne
	zamrażarki laboratoryjne
0	1

all the above technical data refer to standard units (without optional accessories)

* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K= +/- (T average max. - T average min.) / 2

** - other power supplies on request


1 - depth doesn't include 50 mm of power cable

2 - on uniformly loaded surface

3 - reinforced shelf

4 - reinforced version

OPTIONS AND ACCESSORIES



Perforated shelf

Order number: */PO

Order number: */PP

Full shelf with hole



Order number: */PW

Reinforced shelf



Order number: KUW GN*/*

Stainless steel cuvettes





ſ

KG	Order number: */W	Reinforced version
	Order number: OWW/OWW LED	Interior lighting
LAB DESK	Order numberLabDesk	LabDesk software
>0<	Order number: BRT/*/L or IQ/OQ/PQ	Calibration and IQ, OQ, PQ qualification
DIN 3.2	Order number: */3.2	Over temperature protection 3.2 class according to DIN 12880
+	Order number: BPP 12	Battery backup for display
	Order number: PORT ALARM	Dry alarm contact
(((●)))	Order number: KD	Access control

