

Data sheet

×





1

type	
TECHNICAL DATA	
air convection	
chamber capacity [l]	
working capacity [l]	
number of boxes 133x133x50mm (option) [pcs]	
controller	
display	
insulation type	
TEMPERATURE	
TEMPERATURE AND HUMIDITY	
temperature range [°C]	
Working temperature range without humidity [°C]	
Temperature variation (spatial) at 40°C [+/-°C]	
Temperature fluctuation (time) at 40°C [+/-°C]	
Working temperature range with humidity [°C]	
temperature resolution every [°C]	
Temperature variation (spatial) at 40°C, 75% RH [°C]	
Temperature fluctuation (time) at 40°C, 75% RH [°C]	
Temperature variation (spatial) at 25°C, 60% RH [°C]	
Temperature fluctuation (time) at 25°C, 60% RH [°C]	
cooling time from +20°C to -80°C [min]	
heating time in case of power failure -80°C to -60°C [min]	
Temperature accuracy at 20°C [+/-°C]*	
temperature fluctuation at 37°C [+/-°C]*	
temperature fluctuation at 105°C [+/-°C]*	
temperature fluctuation at 4°C [+/-°C]*	
temperature fluctuation at -20°C [+/-°C]*	
temperature fluctuation at -80°C [+/-°C]*	
temperature variation at 25°C and 60%rH [+/-°C]*	
temperature variation at 37°C [+/-°C]*	
temperature variation at 105°C [+/-°C]*	
temperature variation at 4°C [+/-°C]*	
temperature variation at -20°C [+/-°C]*	
temperature variation at -80°C [+/-°C]*	
temperature fluctuation at 25°C and 60%rH [+/-°C]*	
Temperature recovery time after 30 seconds door opening at 37°C [min]	
temperature protection	
CO2	
CO ₂ range [%]	
CO ₂ resolution every [%]	
CO ₂ measurement	
CO ₂ recovery time after 30 seconds door opening at 5 Vol% CO2 [min]	
relative humidity range [%]	
humidity resolution every [%]	
Bank: ING BŚ o/Wodzisław Śląski Nr rachunku: 90 1050 1403 1000 0022 0879 5498 Nr rej. w BDO 000005609 NIP: 647-216-26-87 REGON: 276111984 Sąd Rejonowy w Gliwicach, X Wydział Gospodarczy KRS 0001009595	2/5



humidity variation at 25°C and 60% rH [%rH]
Stabilność wilgotności w 25°C i 60%rH [%rH]
Humidity variation (spatial) at 40°C, 75% RH [+/-%RH]
Humidity fluctuation (time) at 40°C, 75% RH [+/-%RH]
Humidity variation (spatial) at 25°C, 60% RH [+/-%RH]
Humidity fluctuation (time) at 25°C, 60% RH [+/-%RH]
Recovery time to set values after 30 sec door open at 40°C, 75% RH [min]

×

CHAMBER	
door type	
interior	
B Smart	
C Smart	
CS Smart	
P Smart	
PS Smart	
Smart	
IG Smart	
C Smart PRO	
CS Smart PRO	
P Smart PRO	
PS Smart PRO	
Smart PRO	
IG Smart PRO	
housing	
B Smart	
C Smart	
CS Smart	
P Smart	
PS Smart	
Smart	
IG Smart	
C Smart PRO	
CS Smart PRO	
P Smart PRO	
PS Smart PRO	
Smart PRO	
IG Smart PRO	





overall dims [mm] /1/	
width A	
height B	
depth C	
internal dims [mm]	
width D	
width D'	
height E	×
depth F	
depth F'	
depth G	
height G	
height H	
height I	
shelves (standard max)	
max shelf workload [kg] /2/	
number of internal chambers	
number of drawers	
max drawer workload [kg]	
- reinforced shelf version (PW) [kg] /3/	
max unit workload [kg]	
- reinforced unit version (W) [kg] /4/	
External water tank capacity [I]	
weight [kg]	
ELECTRICAL PARAMETERS	
Energy consumption at 37°C [Wh/h]	
voltage**	
Energy consumption at 25°C, 60% RH [Wh/h]	
Energy consumption at 40°C, 75% RH [Wh/h]	
nominal power [W]	
refrigerant	
Noise level [db(A)]	
warranty	
manufacturer	
txt_opis_pt	
PL typ urządzenia	
img_photo	
The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.	
nazwa www pl	
nazwa www EN	
nazwa www ES	
ekran_grafika	





OPTIONS AND ACCESSORIES



(((●)))

СО2

Order number: LANK	LAN cable
Order number: KD	Access control
Order number: ZLN-UT/CO2	$\rm CO_2$ back up system
Order number: ZLN-UT/STP12 / 16	Boxes for samples
Order number: ZLN-UT/ST12 / 16	Rack with drawers

