

Data sheet

(+48) 32 453 91 70

info@pol-eko.com.pl

in

www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski

ul. Kokoszycka 172 C

ZLW-T 300 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer $\,$
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download



Smart PRO - preview screen





1

(+48) 32 453 9170⋈ info@pol-eko.com.plwww.pol-eko.com.pl

127


POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

ZLW-T 300 Smart PRO type **TECHNICAL DATA** air convection forced 310 chamber capacity [I] 213 working capacity [I] controller microprocessor PID display 7" full colour touch screen **TEMPERATURE** -40...0 temperature range [°C] temperature resolution every ... $[^{\circ}C]$ 0,1 temperature fluctuation at -20°C [+/-°C]* 1,5 temperature variation at -20°C [+/-°C]* 1,8 temperature protection class 3.2 to DIN 12880 (option)

CHAMBER	
door type	solid
interior	
P Smart PRO	acid-proof stainless steel to DIN 1.4301
PS Smart PRO	acid-proof stainless steel to DIN 1.4301
housing	
P Smart PRO	powder coated sheet
PS Smart PRO	stainless steel polished

overall dims [mm] /1/

width A	820
height B	1730
depth C	810
internal dims [mm]	
width D	450
width D'	520
height E	1120
depth F	520
depth F'	530
height H	900



shelves (standard max)	3 6
max shelf workload [kg] /2/	10
- reinforced shelf version (PW) [kg] /3/	50
max unit workload [kg]	80
- reinforced unit version (W) [kg] /4/	160
weight [kg]	185





⟨+48⟩ 32 453 91 70□ info@pol-eko.com.pl⊕ www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

oltage**	230V 50-60Hz
ominal power [W]	450
efrigerant	R290 / GWP=3
arranty	24 months
nanufacturer	POL-EKO
ct_opis_pt	all the above technical data refer to standard units (without optional accessories) * - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as: K= +/- (T average max T average min.) / 2 ** - other power supplies on request 1 - depth doesn't include 50 mm of power cable 2 - on uniformly loaded surface 3 - reinforced shelf 4 - reinforced version
L typ urządzenia	Laboratory Freezer
ng_photo	ZLW-T-300-Smart-PRO
he photo above is for reference only, may show additional options not acluded in standard equipment. The real appearance, particularly olor and structure of the material may differ from the ones presented the photo.	The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.
azwa www pl	Zamrażarka Laboratoryjna ZLW-T 300 Smart PRO
azwa www EN	Laboratory Freezer ZLW-T 300 Smart PRO
azwa www ES	Congelador de Laboratorio ZLW-T 300 Smart PRO
ekran_grafika	zl_smart_pro
	zamrażarki laboratoryjne

all the above technical data refer to standard units (without optional accessories)

* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K = +/- (T average max. - T average min.) / 2

- ** other power supplies on request
- 1 depth doesn't include 50 mm of power cable
- 2 on uniformly loaded surface
- 3 reinforced shelf
- 4 reinforced version

OPTIONS AND ACCESSORIES



Order number: */PP Perforated shelf



Order number: */PW Reinforced shelf



Order number: KUW GN*/* Stainless steel cuvettes



Order number: */W Reinforced version





(+48) 32 453 91 70info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C



 $((\bullet))$

>O< Order number: BRT/*/L or IQ/OQ/PQ Calibration and IQ, OQ, PQ qualification

DIN 3.2 Order number: */3.2 Over temperature protection 3.2 class according to DIN 12880

Order number: BPP 12 Battery backup for display

ALARM Order number: PORT ALARM Dry alarm contact

Order number: LANK LAN cable

Order number: KD Access control

